

- ALL UNITS AVAILABLE IN 304 or 316 STAINLESS-STEEL

- RJ-180 TOP-LOADERS ARE BASED ON THE RJ-182 UNITS

- MANY AVAILABLE OPTIONS

- OTHER STYLES AVAILABLE See Pass-Thru, Conveyorized, Carousel

PARTS WASHER MODELS - GENERAL COMPARISON

ROTO-JET OF AMERICA COMPANY, INC.



19425 SOLEDAD CANYON ROAD, # 317 SANTA CLARITA, CA 91351

Ph 661-299-2231 Fx 661-299-9239 Email Info@roto-jettoa.com WEB www.roto-jetpartswasher.com



TOP LOADING

MINIMAL FLOOR SPACE
SHOWN IN OPTIONAL STAINLESS-STEEL

MODEL

MODEL	TABLE DIAMETER	MAX LOAD HEIGHT	LOAD CAPACITY POUNDS	WASH PUMP HP	TANK CAPACITY GAL	ELECTRIC HEAT KW	O'ALL WEIGHT LBS.	TURNTABLE DRIVE	WASH NOZZLES	CABINET INSUL.	PRESS. GAUGE	TEMP GAUGE	7-DAY HEAT TIMER	AUTO-REFILL	
RJ-100	24"	18" - 24"	300	3	25	4.5	530	JET	9	Opt	Opt	Opt	Opt	Opt	
RJ-100-PT	24"	18" - 24"	300	3	25	4.5	700	1/15 HP	9	Opt	Opt	Opt	Opt	Opt	
RJ-140	26"	12"-24"	800	5	70	12	1500	1/15 HP	12	STD	Opt	Opt	Opt	Opt	
RJ-160	36"	12"-24"	1000	7.5	120	12	1850	1/15 HP	14	STD	Opt	Opt	Opt	Opt	
RJ-180	SEE 182 SERIES - POWER LIFT LID IF OVER 48" DIA. TURNTABLE								1/2 HP	S.S. - VARIES	STD	Opt	STD	STD	Opt



LAY-DOWN DOOR ROLL-OUT TURNTABLE

DELUXE MODEL
MAXIMIZES OPERATOR
LOADING & UNLOADING

RJ-1A	27"	32"	500	3	70	6	1500	JET	20 Impact	STD	STD	STD	STD	Opt
RJ-1B	36"	36"	500	5	120	12	1850	JET	25 Impact	STD	STD	STD	STD	Opt
RJ-2B	38"	36"	1000	7.5	240	18	3500	1/3	14 S.S.	STD	STD	STD	STD	STD
RJ-3B	50"	36"	1500	10	275	24	4000	1/3	18 S.S.	STD	STD	STD	STD	STD
RJ-4B	56"	36"	2000	15	330	36	4500	1/3	26 S.S.	STD	STD	STD	STD	STD
RJ-5B	66"	36"	2000	20	500	54	6000	1/3	82 Impact-II	STD	STD	STD	STD	STD

Best for TALL PARTS with optional height increases!

SWING-OUT TURNTABLE LOADING

"CANTILEVER"
DOOR FRAME

OUR MOST VERSITILE
MODEL - SHOWN
WITH OPTIONAL
SWING BOOM & HOIST

RJ-111	27"	32"	500	3	50	6	960	JET	20 Impact	Opt	Opt	Opt	Opt	Opt
RJ-121	26"	32"	500	3	50	6	1100	1/15	9	Opt	Opt	Opt	Opt	Opt
RJ-131	26"	32"	500	3	70	6	1250	1/15	9	STD	Opt	Opt	Opt	Opt
RJ-142	26"	40"	800	5	70	12	1500	1/15	12	STD	Opt	Opt	Opt	Opt
RJ-142-ST	26"	40"	800	5	125	12	1700	1/15	12	STD	Opt	Opt	Opt	Opt
RJ-162	36"	42"	1000	7.5	120	12	1850	1/15	15	STD	Opt	Opt	Opt	Opt
RJ-182AA	26"	42"	1000	5	140	12	2500	1/2	12 S.S.	STD	Opt	STD	STD	Opt
RJ-182A	36"	54"	1500	15	225	18	3500	1/2	26 S.S.	STD	Opt	STD	STD	Opt
RJ-182B	40"	60"	2000	15	240	18	4500	1/2	28 S.S.	STD	Opt	STD	STD	Opt
RJ-182C	48"	60"	2000	15	330	18	5500	1/2	30 S.S.	STD	Opt	STD	STD	Opt
RJ-182D	54"	60"	2000	15	400	36	6000	1/2	32 S.S.	STD	Opt	STD	STD	Opt
RJ-182E	60"	60"	2000	20	500	36	6500	1/2	36 S.S.	STD	Opt	STD	STD	Opt
RJ-182F	66"	60"	2000	20	600	48	7000	1/2	38 S.S.	STD	Opt	STD	STD	Opt
RJ-182G	72"	60"	2000	20	725	54	7500	1/2	40 S.S.	STD	Opt	STD	STD	Opt

RINSE - BLOWOFF - DRY - EXHAUST - CORROSION INHIBIT STAGES AVAILABLE

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE, NOT RESPONSIBILE FOR ERRORS OR OMISSIONS. REFER TO SEPARATE MODEL BULLETINS FOR MORE INFORMATION



NON-CONTACT HEATERS

SOLUTION FILTERING



OIL SKIMMING OR BULK OIL REMOVAL

SLUDGE DRAG-OUT CONVEYORS



HIGH HP AND HIGH PRESSURE PUMPS

OSCILLATING SPRAY BARS

