



ROTO-JET OF AMERICA COMPANY, INC.

19425 SOLEDAD CANYON ROAD, SUITE 317 * SANTA CLARITA, CA 91351

Ph 661-299-2231 * Fx 661-299-9239 * Email: sales@roto-jet.com * WEB www.roto-jetpartswasher.com

MODEL RJ-2B



SPECIFICATIONS

Height	87"
Width	66"
Depth	72"
Depth - Overall with Door Open	116"
Turntable O.D. and Parts Basket I.D.	38" and 35" x 6" H.
Working Capacity - Height	38"
Working Capacity - Load	1,000
Height from floor to bottom of Parts Basket	36"
Solution Capacity	180 GAL
Wash Pump Motor	7.5 HP
Pump Capacity - Flow x Manifold Pressure	110 GPM x 60 PSI
Wash Jets	14
Turntable Drive Motor	1/3 HP
Heating Capacity (1 x 18 Kw) w/Adjustable "Probe" Thermostat	18 KW
Std Power 230V/460V 3Ph 60Hz 208VAC, 1Ph, Overseas Power Avail.	3P 230V-64A / 460V-32A
Vapor Exhaust Stack (nominal diameter)	12"
Fresh Water Inlet for Auto-Fill x Main Tank Drain Outlet	1/2" NPT x 2" NPT
Weight in Pounds	3,300 LBS.

STANDARD OPTIONS

Part

10 HP Wash Pump - adds 7A @ 230V or 4A @ 460V (rec. 24 KW heat)	2B-11
24-Hour/7-Day Heating System Timer	2B-20
Automatic Refill with Low-Water Shut Off	2B-21
Thermal Insulation	2B-24
S.S. Solution Temperature Thermometer	2B-26
Pressure Gauge	2B-68
Stainless Steel Wash Nozzles	2B-34
15" Diameter x 4" High "Drop-Lid" Small Parts Basket	2B-25
Mid-Level Spray Bar w/Isolation Valving	2B-28
Gas Heat Std-Capacity "Econo" Controls" 180,000 BTU Forced Draft	2B-33-1
Gas Heat Hi-Capacity "Industrial" Controls 250,000 BTU Forced Draft	2B-33-2
Wash Pump "Downstream" Polishing Bag Filter #8 x 30	2B-42
Fresh Water Rinse to Tank or Drain w/Auto Diverter 10 Jets @ 3 GPM	2B-43
"Econo" Rinse" Stage w/auto-divert, internal "pod" tank, 1/2" air pump	2B-43-1
"Full" Recirculating Stage w/auto-divert, internal tank, heat, 3 HP pump	2B-43-2
Shop Air Blow Off with 6 "Flex" Adjustable Nozzles @ 8-26 CFM each	2B-45
Vapor Exhaust Stage 1/2 HP	2B-47
HD 12" SS Oil Skimmer w/24-HR/7-Day Timer	2B-48
HD 20" SS Oil Skimmer w/24-HR/7-Day Timer	2B-48-1
Digital Cycle Timer (1 each per stage)	2B-51
DEMA Injector Valve in Water Line for Rinse Stage	2B-54
Additional 6 Kw Heat for 24 Kw total (2 x 12 Kw)	2B-56
Heated Drying Stage 30 KW, 3Hp High-Volume Fan, Controls	2B-45-HABO
"Bottom Filtering" System 2 Hp Pump, #8 x 30 Bag Filter	2B-58
Coated Parts Basket for Parts Protection	2B-59
Height Change +/- 6" Maximum	2B-60
Turntable Load Capacity to 1,500 Lbs (50% Increase)	2B-61

STD
STD
STD
STD
STD
STD

Stainless-Steel Construction Available

Many other options available - call us!

EFF. 01-JAN-14, SUBJECT TO CHANGE WITHOUT NOTICE, NOT RESPONSIBLE FOR ERRORS OR OMISSIONS
LOCAL CODE REQUIREMENTS ARE THE RESPONSIBILITY OF THE PURCHASER

MANUFACTURER OF HIGH-SPEED INDUSTRIAL PARTS WASHERS