

WHIRLWASH-L

Alkaline Spray-Wash Detergent

WHIRLWASH-L is a non-hazardous, biodegradable rust-inhibited alkaline liquid concentrate formulated for the rapid and safe cleaning of electrical equipment, aircraft components or parts **requiring low residue** in aqueous cabinet and conveyerized parts washers. *Safe on steel, iron, aluminum and other sensitive metals, rubber & plastic.*

Applications

Quickly removes grease, oils, carbon, cutting and forming lubricants and other soils.

- Leaves no residue after rinsing to avoid conductivity problems in motor windings. Will not attack electrical insulation and varnishes.
- Contains no glycol ethers, HAPS or VOCs, and is biodegradable and environmentally safe.
- Long bath life and minimal concentrations provide exceptional value with low overall use costs.

Provides operator safety, will not erupt when mixed in hot water like caustic-based products.

- Will not build excess foam in spray cabinets at normal operating temperatures (above 140°F).
- Contains no silicone to interfere with new coatings or paint.
- **Aerospace qualified.** Conforms to Boeing D6-17487, Douglas CSD#1 and AMS 1526B.
- Excellent performance with ultra-filtration systems.

Instructions

Designed for use in hot spray pressure cabinet systems, conveyor-type washers and immersion cleaning equipment. Can be used in manual pressure wash applications. Operate equipment according to manufacturer's instructions.

For Light to Medium Duty Cleaning: Use 2 to 4 ounces of concentrate per gallon of system water.

For Heavy Duty Cleaning: Use 5 to 8 ounces of concentrate per gallon of system water.

WHIRLWASH-L mixes readily and may be added to an opened tank of hot water agitation. It will not erupt in hot water like other caustic-based products.

Solution temperature operating range is from 140F to 190F with typical cleaning times of 5 to 30 minutes.

Rinse parts after washing.

To maintain correct product concentration levels, use the WHIRLWASH-L Titration Test Kit.

QUANTITY

1 Gallon =
128 Fluid
Ounces

Technical Data

Form	Liquid
Color	Amber
pH (when diluted for use)	Approx. 12
Rinseability	Excellent
VOC	None

SAMPLE

FOR INDUSTRIAL
USE ONLY.
PROPERLY DISPOSE
OF EMPTY
CONTAINER.

For Use Precautions and First Aid Information, Please See the Material Safety Data Sheet

CHEMICAL EMERGENCY HOTLINE

1-800-246-2890



ROTO-JET OF AMERICA COMPANY, INC.

19425 Soledad Canyon Road, Ste 317 • Santa Clarita, CA 91351
PH 661-299-2231 • FX 661-299-9239 • WEB www.roto-jet.com